## **TECHNICAL INFORMATION**

Content: 100% Recycled Polyester (65% Pre-/35% Post-Consumer)

Width: 66" / 168 cm	Weight: 9.872 oz./linear yard / 306.07 g/lm Finish: None		
Backing: Acrylic			
Approx. Repeat: 0.063 in/0.16 cm H, 0.063 in/0.16 cm V	Directional: Yes	Railroaded: No	
PERFORMANCE	Results		
FERFORMANCE	Results		
Colorfastness to Crocking AATCC 8	Dry: Grade 4 min / Wet: Grad	e 3 min	

## FLAMMABILITY

ASTM E84 (Unadhered) Class 1 or A California Technical Bulletin 117-2013 NFPA 260/UFAC Class 1

# **REDUCED ENVIRONMENTAL IMPACT**

This product is GREENGUARD Gold Certified for low chemical and particle emissions to UL standard UL 2818 and may contribute to LEED certification. For complete information visit mayerfabrics.com and UL.com/gg.

Eco System<sup>®</sup> Sustainable. Attainable at Mayer Fabrics.

# **CLEANING INFORMATION**

## WS: Water/Solvent Cleaner

BC: Bleach Cleanable – 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

### **ADDITIONAL INFORMATION**

Custom Capabilities: All patterns can be custom colored. Minimum yardage applies. Digital Swatch Card Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation. Specifications: Specifications are correct at the time of printing. Current specifications are available on our website.

#### \*\*\*\*

This fabric meets or exceeds these ACT performance guidelines. \*Certification Marks owned by ACT®

> This 100% polyester fabric is included in the Underwriter's Laboratory Fabric Recognition Program. Additional testing of this U.L. recognized component is not required on approved panels from participating manufacturers.





20919