# **TECHNICAL INFORMATION**

Content: 73% Recycled Polyester (47% Pre-/26% Post-Consumer), 27% Polyester

Width: 66" / 168 cm	Weight: 13.072 oz./linear yard / 405.28 g/lm		
Backing: Acrylic	Finish: None		
Approx. Repeat: 0.375 in/0.95 cm H, 0.25 in/0.64 cm V	Directional: Yes	Railroaded: No	
PERFORMANCE	Results		
Colorfastness to Crocking AATCC 8	Dry: Grade 4 min / Wet: Grade 3 min		
Colorfastness to Light AATCC 16	Grade 4 min at 40 hours		

## FLAMMABILITY

ASTM E84 (Unadhered) Class 1 or A California Technical Bulletin 117-2013 NFPA 260/UFAC Class 1

#### REDUCED ENVIRONMENTAL IMPACT

This product is GREENGUARD Gold Certified for low chemical and particle emissions to UL standard UL 2818 and may contribute to LEED certification. For complete information visit mayerfabrics.com and UL.com/gg.

#### **CLEANING INFORMATION**

WS: Water/Solvent Cleaner

BC: Bleach Cleanable – 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

### **ADDITIONAL INFORMATION**

Custom Capabilities: All patterns can be custom colored. Minimum yardage applies.

Digital Swatch Card Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation. Specifications: Specifications are correct at the time of printing. Current specifications are available on our website.

\*\*\*\*

This fabric meets or exceeds these ACT performance guidelines. \*Certification Marks owned by ACT\*

L This 100% polyester fabric is included in the Underwriter's Laboratory Fabric Recognition Program. Additional testing of this U.L. recognized component is not required on approved panels from participating manufacturers.





20919